

F81.2

F81.2 brings the definition, vocal intelligibility and overall clarity that Funktion-One is known for to a small scale cabinet size, making it a highly versatile and cost effective solution for applications including domestic listening, studio monitoring, retail, bars, restaurants and galleries.

Flared bass reflex ports minimise turbulence and maximise our refined cabinet tuning. A high resolution 1" HF device and Funktion-One designed waveguide delivers precise high frequencies to 20kHz.

F81.2 benefits from our minimalist approach to passive crossover design, achieving very low distortion and excellent integration between drivers, to give a stable and engaging image.

NL4 and Phoenix connector variants are combined into a common connector panel, simplifying purchasing and inventory management. Combine with SB10/SB10A or BR115 for compact full range use.

2 x F81.2 with 1 x SB10A makes for an outstanding, highly mobile, self-powered small party system.



- Features:
- High sensitivity/electroacoustic energy efficiency
  - Minimalist passive crossover design for maximum resolution
  - Dual NL4 and Phoenix connector combination as standard
  - Various mounting/rigging options (yoke, wall bracket)
  - M6 rigging points
  - Weather resistant, IP55 version available

Frequency Response (-3dB): 110Hz - 20kHz  
Weight: 7.4kg (16.3lbs)  
Nominal Dispersion: 90° Horizontal x 60° Vertical  
Connectors: 2 x Neutrik NL4 and Phoenix

Driver	Crossover Frequencies	Sensitivity (At 1m)	Power (AES)	Nominal Impedance
8" + 1"	110Hz - Up	98dB at 2.8V	100W	8Ω

\*Measured in free field

Specific crossover settings can be found at [www.funktion-one.com/support](http://www.funktion-one.com/support)

