

## Evo 2

Evo 2 is a medium dispersion, fully horn-loaded, 3-way loudspeaker, which features the latest Funktion-One driver technology and highly refined tuning. It has evolved from the iconic Resolution 2, which has been in the marketplace for more than 25 years.

Evo 2's outstanding performance capabilities and versatile format make it very appealing across a range of live event and install applications, including as a four point club system or two wide flown system for medium sized venues. Its manageable size and innovative Butterfly Plate rigging system enable quick and easy deployment. Evo 2 is perfectly suited to ground stacking for small events, flying singly or in pairs for wider coverage and larger audience areas, or deployed as fills supporting Vero, Evo or Vero VX touring systems.

Evo 2 can be easily adapted between 3-way active (NL8 tri-amp) or 3-way passive mid-hi (NL4 bi-amp). It is available in standard Funktion-One violet finish or durable black PU coating. A foam backed grille can be added for a more discreet appearance and a custom flight case for a pair of Evo 2s is also available.

### Features:

- Full range, stand alone capability
- Fully horn loaded, excellent efficiency
- 'Butterfly plate' rigging system
- Available 3-way active or bi-amped with passive mid-hi
- Optional grille
- Custom flight case
- Integrated M10 points for install use



Frequency Response: 85Hz - 18kHz  
 Low Frequency Response (-10dB): 60Hz  
 Weight: 36kg (80lbs)  
 Nominal Dispersion: 50° Horizontal x 25° Vertical  
 Connectors: 2 x Neutrik NLT4M or NLT8M

Driver	Crossover Frequencies	Sensitivity (at 1m)*	Power (AES)	Nominal Impedance
12" (LF)	45/85Hz - 280Hz	100dB at 2.8V	600W	8Ω
8" (MF)	280Hz - 5kHz	107dB at 4V	200W	16Ω
1" (HF)	5kHz - up	108dB at 4V	75W	16Ω

\*Measured in free field

Specific crossover settings can be found at [www.funktion-one.com/support](http://www.funktion-one.com/support)

