

Evo 2SH

Evo 2SH takes the mid-high waveguide from the Evo 2 and makes it available as a separate, modular system element.

With the same very high efficiency and outstanding audio presentation as the Evo 2, Evo 2SH is useful for installations where reduced weight and size are a priority. The stainless steel metalwork is resistant to corrosion, making it suitable for undercover outdoor applications, such as stadia and other situations where high output and speech intelligibility are required.

Evo 2SH is also useful as fills for larger systems. It can be rigged either way up to accommodate different coverage requirements and has a neatly integrated passive crossover network. Full range audio is achieved by combining Evo 2SH with low frequency reinforcement, such as Evo 2L, F115 Mk2 or F215 Mk2.



Features:

- Extremely high efficiency
- Light weight
- Outstanding audio presentation

Frequency Response: 280Hz - 18kHz
 Low Frequency Response (-10dB): 200Hz
 Weight: 10kg (22lbs)
 Nominal Dispersion: 50° Horizontal x 25° Vertical
 Connectors: 2 x Neutrik NL4

Driver	Crossover Frequencies	Sensitivity (at 1m)*	Power (AES)	Nominal Impedance
8"+1" (MHF)	280Hz - 18kHz	111dB at 4V	200W	16Ω

*Measured in free field

Specific crossover settings can be found at www.funktion-one.com/support

