

PSM15

The Funktion-One PSM15 is a high-performance, triaxial (bi-amped) 15" stage monitor engineered for superior clarity and control in demanding live environments. It delivers a natural and detailed response, with excellent vocal intelligibility and low distortion at high SPL.

The advanced waveguide design provides exceptionally consistent directivity, making the PSM15 inherently less prone to feedback. The 3-way, bi-amped approach enables optimised LF and HF design, resulting in a clearer, stronger vocal range and punchy low frequencies. In live monitoring environments, where vocal clarity, mix definition and feedback control are critical, this translates to a more accurate and stable on-stage reference.

The PSM15 is optimised for ease of handling, featuring M10 flying points for yoke mounting and M8 points for use with a stand adapter. There is also a ground stack board to mount the PSM15 on one or two BR118.2 with adjustable tilt angle for extended low frequency response in drum monitor and DJ monitor applications.

Features:

- Naturally flat response without preset EQ
- Triaxial (3-way) bi-amped design
- Exceptionally consistent directivity
- Advanced waveguide design (70°V x 50°H nominal, rotatable)
- Very high SPL
- High clarity and vocal intelligibility
- High impact bass
- Minimal feedback sensitivity
- Low distortion, even at high SPL
- Compact and discrete aesthetic



Frequency Response: 80Hz - 18kHz

Low Frequency Response (-10dB): 60Hz

Weight: 28kg (62lbs)

Nominal Dispersion: 50° Horizontal x 70° Vertical

Connectors: 2 x Neutrik NLT4M

Driver	Sensitivity (at 1m)*	Power (AES)	Nominal Impedance
15" (LF)	96dB at 2.8V	600W	8Ω
(MHF)	105dB at 2.8V	100W	8Ω

*Measured in half space

Powered by Funktion-One D-Series Amplifiers
www.funktion-one.com/support

